

# KENWOOD

## NX-5200/5300/5400

### NEXEDGE®

NEXEDGE® VHF/UHF / 700-800MHz  
MULTI-PROTOCOL DIGITAL & ANALOG PORTABLE RADIOS



**NXDN®**



**Bluetooth®**



**GPS FleetSync®**  
by KENWOOD



### ● FEATURE HIGHLIGHTS

- **Multi-Protocol** operation in P25 (Phase 1 & 2), NXDN® and Analog protocols
- **Mixed Digital & FM Analog Operation** allows intelligent migration in mixed sites and easy migration with digital radios in other sites
- **Large, Color 1.74" (240 x 180 pixels) Transflective TFT Display** for better interface even in direct sunlight and with use of polarized sunglasses
- **Easy to follow GUI** for at-a-glance operational status checking and Multi-line Text to convey more information
- **4-way Directional-pad (D-pad)** and **2-Position Lever Switch** for intuitive control and operation
- **Built-In GPS Receiver/Antenna** for effective fleet management
- **Built-in Bluetooth® Module**
- **Active Noise Reduction (ANR)** utilizing built-in DSP with two microphones for suppression of ambient noise
- Renowned **KENWOOD Digital Audio Quality**
- **Built-in 56-bit DES Encryption**
- **Optional 256-bit AES Encryption**
- **Built-in Motion Sensor** for life-critical man down detection
- **microSD/microSDHC Memory Card Slot** for increased memory capacity for "Voice & Data"
- **IP67/68 and MIL-STD-810 C/D/E/F/G**

### ● GENERAL FEATURES

- 6 W (136-174 MHz) Models
- 5 W (380-470, 450-520 MHz) Models
- 3 W (700/800 MHz) Models
- Full Key Models (w/ numeric keypad) and Standard Key Models (w/o numeric keypad)
- Maximum of 4,000 CH/Radio capacity, 512 CH/Zone, 128 Zones
- 1 W Loud Speaker Audio

### ● DIGITAL – P25 MODE

- P25 Conventional Trunking (Phase 1 & 2) Protocol
- AMBE+2™ Enhanced Vocoder
- Talk Group ID Lists
- Individual ID Lists
- Caller ID Display
- Remote Monitor/Remote Check
- Radio Inhibit

- Encryption Key Zeroize & Retention
- P25 GPS Location
- Over-the-Air Programming<sup>1</sup>

### ● DIGITAL – NXDN® MODE

- NXDN® Conventional/Type-C Trunking Protocol
- AMBE+2™ VOCODER
- 6.25 & 12.5 kHz Channels
- Over-the-Air Alias
- Over-the-Air Programming<sup>1</sup>
- Paging Call
- Emergency Call
- All Group Call
- Status Messaging<sup>2</sup>
- Remote Stun/Kill<sup>2</sup>
- Remote Check<sup>2</sup>
- Short & Long Data Messages<sup>2</sup>
- GPS Location
- NXDN® Digital Scrambler Included

### ● FM MODES – GENERAL

- Conventional & LTR Zones
- NPSAC (USA only) Channels (±4.0 Modulation)
- FleetSync®/II: PTT ID ANI / Caller ID Display, Selective Group Call, Emergency Status / Text Messages
- MDC-1200: PTT ID ANI / Caller ID Display, Emergency, Radio Check / Inhibit
- QT / DQT & Two-Tone
- Built-in Voice Inversion Scrambler

### ● INTELLIGENT BATTERY SYSTEM (Option)

- System consists of the optional high-capacity Battery Series (KNB-L1/L2/L3/N4), Rapid Charger (KSC-Y32), and Battery Reader (KAS-12) software
- Up to 60 Rapid Chargers can be chain-connected to a PC installed with the KAS-12
- KAS-12 Battery Reader software can display and manage information including battery type, model name, voltage, temperature, discharge cycle, expected life, and remaining capacity
- Up to 5,000 batteries can be managed at a time (requires an additional option)

<sup>1</sup> Requires KENWOOD OTAP Management software.

<sup>2</sup> Requires NX subscriber unit PC serial interface compatible software application (e.g. KENWOOD AVL & Dispatch Messaging software) or hardware (e.g. console).

# Options

**KNB-L1/L2/L3**  
Li-ion Battery Pack  
(IP67/68 Immersion)



**KNB-N4**  
Ni-MH Battery Pack  
(IP67/68 Immersion)



**KBP-8**  
Alkaline Battery Case



**KSC-Y32**  
Rapid Charger



**KSC-32/32S**  
Rapid Charger



**KSC-326/326S**  
Rapid Charger



**KAS-12**  
Battery Reader  
(PC Software)




**KRA-26**  
VHF Helical Antenna  
(Standard Length)



**KRA-27**  
UHF Whip Antenna  
(Standard Length)



**KRA-32**  
700/800MHz Whip Antenna



**KMC-42WD**  
Speaker Microphone (IP67)



**KMC-54W**  
Speaker Microphone  
• 2-mic digital noise cancelling via the radio's DSP  
• 3.5mm-diameter EP jack  
• Complies with MIL-STD 810C/D/E/F/G  
• IP65/67 Dust & Water\*



**KWD-AE30/AE31**  
Secure Cryptographic Module

**KPG-180AP**  
OTAP Manager

**KBH-11**  
Belt Clip



All accessories and options may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

# Main Specifications

	NX-5200	NX-5300	NX-5400
<b>GENERAL</b>			
<b>Frequency Range</b>	136-174 MHz	Type 1: 450-520 MHz Type 2: 380-470 MHz	RX: 763-776, 851-870 MHz TX: 763-776, 793-806, 806-825, 851-870 MHz
<b>Max. Channels Per Radio</b>	1024 (Up to 4000 CH with option)		
<b>Number of Zones</b>	128		
<b>Max. Channels per Zone</b>	512		
<b>Channel Spacing</b>	Analog: 12.5/15/20/25*/30* kHz Digital: 6.25kHz/12.5kHz	12.5/25* kHz 6.25kHz/12.5kHz	12.5/25 kHz 12.5 kHz (6.25 kHz)
<b>Power Supply</b>	7.5V DC ± 20%		
<b>Battery Life</b>	(5-5-90/10-10-80 duty cycle)		
KNB-L1 (2,000 mAh)	10 hours / 6.5 hours		
KNB-L2 (2,600 mAh)	12.5 hours / 8.5 hours		
KNB-L3 (3,400 mAh)	17 hours / 11 hours		
KNB-N4 (2,500 mAh)	12.5 hours / 8.5 hours		
KBP-8 (w/AA x12)	High Power Approx. 11 hours / 8 hours / Low Power Approx. 25 hours / 18 hours		
<b>Operating Temperature</b>	-22°F to +140°F (-30°C to +60°C)		
<b>Frequency Stability</b>	±2.0 ppm	±1.0 ppm	±1.5 ppm
<b>Dimensions/Weight</b> Radio w/battery	(W x H x D) Projections Not Included		
KNB-L1 (2,000 mAh)	2.28 x 5.47 x 1.57 in. (58.0 x 138.9 x 39.8 mm)		13.5 oz (382 g)
KNB-L2 (2,600 mAh)	2.28 x 5.47 x 1.69 in. (58.0 x 138.9 x 42.8 mm)		14.3 oz (406 g)
KNB-L3 (3,400 mAh)	2.28 x 5.47 x 1.90 in. (58.0 x 138.9 x 48.2 mm)		15.8 oz (449 g)
KNB-N4 (2,500 mAh)	2.28 x 6.55 x 1.91 in. (58.0 x 166.4 x 48.5 mm)		20.4 oz (579 g)
KBP-8	2.64 x 8.59 x 1.76 in. (67.0 x 218.3 x 44.6 mm)		Approx. 25.1 oz (712 g)
<b>FCC ID</b>	Type 1: K44431400 Type 2: K44431500	K44431500 K44431501	ALH442000
<b>IC Certification</b>	Type 1: 282F-431400 Type 2: 282F-431501	-	282D-442000

\*25 and 30 kHz are not included in the models sold in the USA or US territories. Analog measurements made per TIA 603 and specifications shown are typical. P25 Digital measurements made per TIA 102CAA and specifications shown are typical. Specifications are subject to change without notice, due to advancements in technology. .

	NX-5200	NX-5300	NX-5400
<b>RECEIVER</b>			
<b>Sensitivity</b>	NXDN® 6.25 kHz Digital (3% BER) NXDN®12.5 kHz Digital (3% BER) P25 Digital (5% BER) P25 Digital (1% BER) Analog (12dB SINAD)	0.20 µV 0.25 µV 0.25 µV 0.40 µV 0.25 µV	
<b>Selectivity</b>	P25 Digital Analog @ 12.5 kHz Analog @ 25 kHz	67 dB	60 dB 64 dB
<b>Intermodulation</b>		73 dB	75 dB
<b>Spurious Rejection</b>	80 dB		75 dB
<b>Audio Distortion</b>	3%		
<b>Audio Output Power</b>	500 mW/8   (3% Distortion) / 1,000 mW /8   (5% Distortion)		
<b>TRANSMITTER</b>			
<b>RF Power Output Power</b>	6 W to 1 W	5 W to 1 W	3 W to 1 W
<b>Spurious Emission</b>	-70 dB		
<b>FM Hum &amp; Noise</b>	Analog @ 12.5 kHz Analog @ 25kHz	40 dB 45 dB	
<b>Audio Distortion</b>	2%		
<b>Emission Designator</b>	16K0F3E, 11K0F3E, 8K10F1E, 8K10F1D, 8K10F1W, 8K30F1E, 8K30F1D, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D		16K0F3E, 14K0F3E, 11K0F3E, 8K10F1E, 8K10F1D, 8K10F1W, 8K30F1E, 8K30F1D, 8K30F7W, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D

The Bluetooth word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. SD and microSD are trademarks of SD-3C, LLC in the United States, and/or other countries. AMBE+2™ is a trademark of Digital Voice Systems Inc. Windows™ is a registered trademark of Microsoft Corporation. NXDN® is a trademark of JVCKENWOOD Corporation and Icom Inc. NEXEDGE™ is a registered trademark of JVCKENWOOD Corporation. FleetSync™ is a registered trademark of JVCKENWOOD Corporation.

# Applicable MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
<b>Low Pressure</b>	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II	500.5/Procedure I, II
<b>High Temperature</b>	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II	501.5/Procedure I, II
<b>Low Temperature</b>	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II	502.5/Procedure I, II
<b>Temperature Shock</b>	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II	503.5/Procedure I
<b>Solar Radiation</b>	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I	505.5/Procedure I
<b>Rain</b>	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III	506.5/Procedure I, III
<b>Humidity</b>	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4	507.5/Procedure II
<b>Salt Fog</b>	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4	509.5
<b>Dust</b>	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III	510.5/Procedure I
<b>Vibration</b>	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I
<b>Shock</b>	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV	516.6/Procedure I, IV
<b>Immersion</b>	-	-	-	512.4/Procedure I	512.5/Procedure I
<b>International Protection Standard</b>					
<b>Dust &amp; Water Protection</b>	IP54/55				
<b>Immersion</b>	IP67/68*				

\*IP68=1m/2H

# KENWOOD

JVCKENWOOD USA Corporation  
Communications Sector Headquarters  
3970 Johns Creek Court, Suite 100, Suwanee, GA 30024-1265  
Order Administration/Distribution  
P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745  
[www.kenwood.com/usa](http://www.kenwood.com/usa)

JVCKENWOOD Canada Inc.  
Canadian Headquarters and Distribution  
6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8  
[www.kenwood.com/ca](http://www.kenwood.com/ca)



ISO9001 Registered  
JVCKENWOOD Corporation